



Outrageously Dependable®

Group Size	Terminal	Part #	SAE Ratings			Free Replacement Months
			CCA 30 sec./0°F	CA 30sec./32°F	RC min 25amp/80°F	
MARINE / RV • 12 Volt						
24DC	M	PF-24DC-7	540	675	135	12
24DC	M	SRM-24 ¹	550	690	140	12
24DP	M	HD24-DP ¹	405	505	100	12
24MS	M	24M-RD	400	500	75	12
24MS	M	PF-24M-4	490	610	90	12
24MS	M	24M-HD	500	625	95	12
24MS	M	PF-24M-7P	795	990	130	12
24MS	M	24M-XHD	800	1000	135	12
27DC	M	PF-27DC-7	665	830	155	12
27DC	M	SRM-27 ¹	600	750	160	12
27MS	M	PF-27M-7P	795	990	180	12
27MS	M	27M-XHD	800	1000	182	12
29DC	M	PF-29DC-7	665	830	200	12
29DC	M	SRM-29 ¹	675	845	210	12
4DDC	M	SRM-4D ¹	1314	1645	390	6
31	UT	31TMXU	700	1000	200	6
MARINE / RV AGM • 12 Volt						
34M	M	34M-AGM ¹	800	1000	125	36
31M	M	31M-AGM ¹	800	1190	190	36
COMMERCIAL* • 12 Volt						
29H/30H	A	29H-VHD	660	825	160	18
29NF	A	29NF-VHD	420	525	77	6
31A	A	31P-VHD	660	825	160	18
31A	A	31P-ECL	700	875	190	18
31A	A	31P-LHD	750	940	180	18
31A	A	PF-31P-6HD	940	1175	190	12
31A	A	31P-MHD	950	1190	195	18
31A	A	PF-31P-7	1000	1250	185	12
31T	T	31-VHD	660	825	160	18
31T	T	31-ECL	700	875	190	18
31T	T	31-LHD	750	940	180	18
31T	T	PF-31S-6HD	940	1175	190	12
31T	T	31-MHD	950	1190	195	18
31T	T	PF-31S-7	1000	1250	185	12
31T	T	31-XHD	1000	1250	195	18
3EE	A	3EE-VHD	400	500	90	6
3ET	A	3ET-VHD	460	575	105	6
4D	A	PF-4D-7	990	1235	290	6
4D	A	4D-XHD	1000	1250	295	6
4DLT	A	4DLT-VHD	860	1075	235	6
8D	A	8D-XHD	1155	1445	380	6
8D	A	PF-8D-7	1390	1735	440	6

8D	A	8D-MHD	1400	1750	450		6
8D	C	8D-1075	1100	1340	325		6
8D	B	8D-1400	1400	1700	430		6
8D	C	8D-1400	1400	1750	400		6
COMMERCIAL AGM* • 12 Volt							
31A	A	31P-AGM7 ¹	810	1200	190		36 ⁽²⁾
31T	T	31-AGM7 ¹	810	1200	190		36 ⁽²⁾
4D	L	AGM4D	-	-	200Ah		6
8D	L	AGM8D	-	-	250Ah		6
COMMERCIAL* • 8 Volt							
	A	1-8V-VHD	520	650	100		6
COMMERCIAL* • 6 Volt							
1	A	1-VHD	640	800	130		6
2	A	2-XHD	610	765	160		6
3EH	A	3EH-VHD	875	1095	250		6
4	A	4-XHD	1000	1250	295		6
LAWN & GARDEN • 12 Volt							
22F	A	SP-22F	450	560	75		6
22NF	A	SP-22NF	390	490	62		6
45	A	SP-45	480	600	74		6
70	S	SP-70	525	655	85		6
U1	X	SP-18	145	180	12		6
U1	X	SP-30	250	310	30		6
U1	X	SP-35	300	375	33		6
U1	X	SP-40	340	425	41		6
U1R	X	SP-18R	145	180	12		6
U1R	X	SP-30R	250	310	30		6
U1R	X	SP-35R	300	375	33		6
Group Size	Terminal	Part #	SAE Ratings				Free Replacement Months
			CCA 30 sec./0°F	RC min 25amp/80°F	RC min 75amp/80°F	Ah 20 Hr	
GOLF CAR⁽³⁾ • 6 Volt							
GC2	UTL, UT, S	GC2-ECL ⁴	-	447	115	225	12
GC2	UTL, UT	GC2-HCL ⁴	-	383	105	210	12
GC2	UTL	PF-GC2 ⁴	-	383	105	210	6
GC2	UTL, UT	GC2-RD ⁵	-	415	107	208	12
GC2	UTL, UT	GC2-HD ⁵	-	445	115	216	12
GC2	UTL, UT, S	GC2-XHD ⁵	-	475	122	232	12
GC2	UTL, UT, S	2300	-	517	140	242	12
GC2	UTL, UT, S	2400	-	562	154	251	12
GC2	M	GC2-HD-AGM	-	475	124	210	6
GC2	T	AGC2N	-	492	-	220	6
GOLF CAR⁽³⁾ • 8 Volt							
GC8	UTL, UT	GC8-HCL ⁴	-	295	117@56A	170	12
GC8	UTL	PF-GC8 ⁴	-	277	110@56A	160	6
GC8	UTL, UT	GC8-HD ⁵	-	337	128@56A	170	12
GC8	UTL	GC8-XHD	-	345	95	183	12
GOLF CAR⁽³⁾ • 12 Volt							
GC12	UTL	12VGC	-	292	77	155	6
FLOOR MACHINE (Sweeper, Scrubber)⁽³⁾ • 6 Volt							
	S	2500	-	570	159	255	6
	S	2500HC	-	635	178	280	6
	S	3050	-	715	185	310	6
	S	3050HC	-	790	215	340	6
	L	L-16	-	810	225	380	6

	S	L-16	-	810	225	380	6
	L, S	L-16HC	-	940	250	420	6
FLOOR MACHINE (Sweeper, Scrubber) ⁽³⁾ • 12 Volt							
	S	1850	-	398	106	200	6
	S	1850HC	-	443	117	220	6
	M	1850-AGM	-	518	125	234	6
MULTI-PURPOSE DEEP CYCLE ⁽³⁾ • 6 Volt							
	S	SRM-1	-	165	44	95	6
MULTI-PURPOSE DEEP CYCLE ⁽³⁾ • 12 Volt							
	S, A	SRM-8D	-	455	106	240	6
STARTING • 6 Volt							
17HF	A	17HF	360	115	-	-	6
19L	A	19L	525	110	-	-	6
STARTING • 12 Volt							
	A	17TF-VHD	625	150	-	-	6
	A	911	300	65	-	-	6
6TL	A	6TL ³	825	215	-	-	6
WITH NO EXCHANGE, CORE CHARGE WILL APPLY							